



TTM1428-02FC

Oilite[®] M-Series Food- Contact

Thrust

Sintered Bronze Impregnated with Food
Grade Mineral Oil: FDA 21 CFR
172.878.

Temp Range -23°C to +100°C

Dimensions & Tolerances

Nominal ID: 14 mm
ID Max: 14.25 mm
ID Min: 14 mm
Nominal OD: 28 mm
OD Max: 28.25 mm
OD Min: 27.75 mm
Length: 2 mm ± 0.065
Weight: 0.0135 lbs / 6.1 g

Press Fit

Housing Bore: 28.17943 mm ± 0.013
Shaft Diameter: 14.12988 mm ± 0.005

Temperature

Max Temp F / C: 220 / 104
Min Temp F / C: -10 / -23

Pressure Ratings

Max P: 13.78 (N/mm²)
Max V: 6.1 (m/s)
Max PV: 1.75 (N-M/mm²-s)
Calculated P: 0 (N/mm²)
Calculated V: 0 (m/s)
Calculated PV: 0 (N-M/mm²-s)

Material Specifications

Lubrication: Self-Lubricating
Regulations: USDA-H1 Certified
Food Contact Certified
Lead-Free
Conflict Free
RoHS Certified
Reach Certified
Engineering Preferences: Conducts Electricity
Corrosion Resistant
Specifications Met: SAE 841
ASTM B-438 GR 1 TYPE 2
CT-1000-K26