

# TTM2550-03

## Oilite® M-Series Metric

### Thrust

Sintered Bronze Impregnated with  
Synthetic Performance  
Difference™ AM1-SPD™.

Largest Selection of Metric Sizes World  
Wide.

Temp Range -37°C to +149°C



### Dimensions & Tolerances

Nominal ID: 25 mm  
ID Max: 25.25 mm  
ID Min: 25 mm  
Nominal OD: 50 mm  
OD Max: 50.38 mm  
OD Min: 49.62 mm  
Length: 3 mm ±0.065  
Weight: 0.0645 lbs / 29.3 g

### Press Fit

Housing Bore: 50.28758 mm ±0.013  
Shaft Diameter: 25.09204 mm ±0.005

### Temperature

Max Temp F / C: 300 / 149  
Min Temp F / C: -35 / -37

### Pressure Ratings

Max P: 13.78 (N/mm<sup>2</sup>)  
Max V: 6.1 (m/s)  
Max PV: 1.75 (N-M/mm<sup>2</sup>-s)  
Calculated P: 0 (N/mm<sup>2</sup>)  
Calculated V: 0 (m/s)  
Calculated PV: 0 (N-M/mm<sup>2</sup>-s)

### Material Specifications

Lubrication: Self-Lubricating  
Regulations: Lead-Free  
Conflict Free  
RoHS Certified  
Reach Certified  
Engineering Preferences: Conducts Electricity  
Corrosion Resistant  
Specifications Met: SAE 841  
ASTM B-438 GR 1 TYPE 2  
CT-1000-K26