



## TTMP2540-04

### Oilite<sup>®</sup> M-Series Metric/PLUS

#### Thrust

PTFE Additive-Reduced Friction  
Synthetic Oilite<sup>®</sup>/Plus-SPD<sup>™</sup>. Extreme  
Performance-Unique Applications.

Temp Range -50°C to +149°C

#### Dimensions & Tolerances

Nominal ID: 25 mm  
ID Max: 25.25 mm  
ID Min: 25 mm  
Nominal OD: 40 mm  
OD Max: 40.38 mm  
OD Min: 39.62 mm  
Length: 4 mm  $\pm 0.065$   
Weight: 0.0452 lbs / 20.5 g

#### Press Fit

Housing Bore: 40.29458 mm  $\pm 0.013$   
Shaft Diameter: 25.09833 mm  $\pm 0.005$

#### Temperature

Max Temp F / C: 300 / 149  
Min Temp F / C: -60 / -51

#### Pressure Ratings

Max P: 13.78 (N/mm<sup>2</sup>)  
Max V: 6.1 (m/s)  
Max PV: 1.75 (N-M/mm<sup>2</sup>-s)  
Calculated P: 0 (N/mm<sup>2</sup>)  
Calculated V: 0 (m/s)  
Calculated PV: 0 (N-M/mm<sup>2</sup>-s)

#### Material Specifications

Lubrication: Self-Lubricating  
Regulations: Lead-Free  
Conflict Free  
RoHS Certified  
Reach Certified  
Engineering Preferences: Conducts Electricity  
Corrosion Resistant  
Specifications Met: SAE 841  
ASTM B-438 GR 1 TYPE 2  
CT-1000-K26