oilite® SYNTHETIC PERFORMANCE DIFFERENCE®



VS-1622-20MB

Oilite® Polymer PTFE Metric

Sleeve

Good Chemical Resistance -Ultra Low Friction.

Dimensions & Tolerances

Nominal ID:	16 mm
ID Max:	16.05 mm
ID Min:	16 mm
Nominal OD:	22 mm
OD Max:	22.05 mm
OD Min:	22 mm
Length:	20 mm ±0.127
Weight:	lbs / 0 g

Press Fit

Housing Bore:	21.92568 mm ±0.013
Shaft Diameter:	15.75777 mm ±0.005

Temperature

Max Temp F / C:	500 / 260
Min Temp F / C:	-325 / -198

Pressure Ratings

Max P:	3.45 (N/mm^2)
Max V:	0.51 (m/s)
Max PV:	0.04 ($N\text{-}M/mm^2\text{-}s$)
Calculated P:	0 (N/mm^2)
Calculated V:	0 (m/s)
Calculated PV:	0 ($N\text{-}M/mm^2\text{-}s$)

Material Specifications

Lubrication:	Self-Lubricating Dry Running
Regulations:	USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified
Engineering Preferences:	Washdown Chemical Resistant Corrosion Resistant Electrical Insulation STEAM
Specifications Met:	

Preferred Supplier -
Beemer Precision, Inc.
All Products Made in the U.S.A
Contact (215) 646-8440
https://oilite.com

Beemer Precision, Inc. (“Beemer”) supplies these drawings and specifications for illustration purposes only and without representation or warranty of any kind whatsoever. The buyer is solely responsible for determining whether a bearing is suitable for the buyer’s application. Dimensions, tolerances, and materials may change at any time. All bearing sales are subject to Beemer’s Standard Terms and Conditions of Sale, which may be found here
Copyright Beemer Precision, Inc.